



T 748V2 Audio Video Receiver



At NAD, bringing you joyful sound is at the heart and soul of everything we do. This is unmistakable when you first listen to our performance driven T 748V2 AV Receiver, now with a second zone. With 7 channels of ultra low distortion power, it creates a seamless and immersive sound field for today's HD soundtracks. The T 748V2 delivers everything you need for a moving home cinema experience without any costly or complex features, occupying that sweet spot of maximum value.



Features

> Incredible Video

The T 748V2 offers killer video performance and the latest digital video technology, including 3D video at resolutions up to 1080p. Analogue video, Audio Return Channel, and Consumer Electronic Control are all supported on HDMI for simple integration with your digital video devices. You'll also enjoy the new Zone 2 feature.

> 'Music First' Audio

Popular surround sound formats, including Dolby TrueHD and DTS Master Audio, are decoded using the latest generation of high-speed DSP. Stereo source material can be converted to surround sound using our exclusive EARS surround mode, praised by reviewers for its natural sound quality.

> Easy Control and Command

In contrast to many AV receivers, the T 748V2 is incredibly simple and user-friendly. We include all the


essentials and none of the fluff, making setup and control easy and straightforward. For convenience, we have also included connections for external control systems like Crestron, AMX, Nevo, etc.

> Five Powerful AV Presets

While other AV receivers only offer one global setting for all sources, you can customise the T 748V2 for various systems or material (Blu-ray player, action movie, music, gaming, etc.) with specific speaker settings and surround modes. Another thoughtful touch is the ability to rename Inputs to match your components.

> Get More Music


If you love your iPod music, simply add our IPD 2 Dock, which shows your song information on the T 748V2's On Screen video display. Radio lovers will appreciate the T 748V2's highly sensitive FM/AM tuner, 30 station presets, and RDS support. Or add our DB 2 digital DAB+ module (230V only) for high quality digital radio.




© NAD T 748V2

Total Width 435mm

Total Depth 397mm



Total Height
167mm



Specifications

AMPLIFIER SECTION	T 748V2
FTC	2 x 80W
Full Disclosure Power (all channels driven simultaneously)	7 x 40W
IHF Dynamic Power	8 Ohms 4 Ohms
	2 x 110W 2 x 160W
Total Harmonic Distortion at rated power	<0.08%
IM distortion at rated power	<0.08%
Damping Factor, 8 ohms	>60
Input Sensitivity and Impedance	250mV/47kiloohms
Frequency Response	±0.5dB (ref. 1kHz, 20Hz-20kHz)
Signal/Noise Ratio	>100dB (ref. rated power at 8 Ohms, A-WTD) >90dB (ref. 1W at 8 Ohms, A-WTD)
TUNER SECTION	
AM SECTION	
Tuning Range	520kHz - 1710kHz (120V version, 10kHz steps) 522kHz - 1620kHz (230V version, 9kHz steps)
Usable Sensitivity	60dBµV
Signal/Noise Ratio	40dB
Total Harmonic Distortion	<1.5%
Loop Sensitivity 20dB S/N	60dBµV
FM SECTION	
Tuning range	87.50MHz - 108.00MHz
Usable Sensitivity	Mono <10dBµV
Signal/Noise Ratio	Mono 65dB Stereo 60dB
Total Harmonic Distortion	Mono 0.25% Stereo 0.5%
Channel Separation	30dB
RDS Decode Sensitivity	28dBµV
GENERAL	
Idle Power	50W
Standby power	<0.5W
Unit Dimensions (WxHxD) - Gross*	435 x 167 x 397mm 17 1/8 x 6 5/8 x 15 11/16 inches**
Net weight	11.5kg (25.3lb)
Shipping weight	14.0kg (30lb)

* Gross dimensions include feet, extended buttons and rear panel terminals.

** Non-metric measurements are approximate. NAD Electronics will not assume any liability for errors being made by retailers, custom installers, cabinet makers, or other end users based on information contained in this document.

Note: Installers should allow a minimum clearance of 55mm for wire/cable management.

NAD

NAD Electronics International reserves the right to change specifications or features without notice. NAD is a registered trademark of NAD Electronics International. All rights reserved. No part of this publication may be reproduced, stored, or transmitted in any form whatsoever without the written permission of NAD Electronics International. © 12/17 13-041 NAD Electronics International.

www.NADelectronics.com