

Name: NAD 6300 Stereo Cassette Deck**Year Released: 1987**

Speed Accuracy	± 1%
Wow & Flutter	<0.03% JIS wtd. RMS <0.05% DIN wtd. Peak
Frequency Response (MPX filter off)	30 Hz-20 kHz ± 3 dB
MPX filter response	Flat within 1 dB to 15 kHz
Harmonic Distortion	Varies with recording level; typically <0.3% at -10 dB
THD at 0dB	< 1.0% (Norma!) <1.5% (CrO ₂ , Metal)
Signal/Noise Ratio re 3% THD at 333 Hz CCIR or A weighting	Dolby Off 59 dB Dolby B 68 dB Dolby C 78 dB
Channel Separation	45 dB at 1 kHz 40 dB broadband
Erase Input Sensitivity/Impedance Maximum input level Output Level at 0 dB Output Impedance	70 dB at 1 kHz 40 mV/10 kΩ 25V 500mV 100 ohms
PHYSICAL SPECIFICATIONS	
Dimensions (W x H x D)	435 x 120 x 280 mm 17.1 x 4.75 x 11in
Net Weight	
Deck	5.9kg (13lb)
Remote Control	1kg (6oz)
Shipping Weight	1.4kg (16.4lb)
Power Consumption	42W-110, 120, 220 or 240 VAC (50/60 Hz)